

DP-3030

# resourceful

- Up to 30 ppm Digital Copying and Printing
- Standard Document Handling Software
- **Standard Network Printer / Scanner / Internet Fax**
- Standard Stackless Duplexing
- Enhanced Security Features

**Panasonic ideas for life**

# DP-3030 – Options & Specifications

## Hard Disk

**Hard Disk Drive Unit**  
DA-HD30  
(Optional Image Memory is required)

## Image Memory Options

**64MB / 128MB**  
DA-SM64B / DA-SM28B

## Fax / Memory Options

**Flash Memory** 4MB Flash Memory / 8MB Flash Memory  
UE-410047F/UE-410048F

**Exit Tray (Inner)**  
DA-XN201

## Paper Exit Options

### Software

#### Accounting System

**Accounting Software**  
DA-WA10  
(Optional Hard Disk Drive Unit and  
Optional Image Memory are required)

#### DD Server System

**DD Server Software**  
DA-W520

**1-bin Finisher**  
DA-F5300

**Exit Tray (Outer)**  
DA-XT200

### G3 Fax

**Fax Communication Board**  
DA-FG300

### Expansion Board

DA-EM600F

## Printer / Network Printer Options

**Printer Controller Module**  
DA-PC301

**Multi-Page Description Language  
Controller Module**  
DA-MC301

**PS/PCL Printer**

## Document Distribution System

**Panasonic Document Distribution System**  
DA-WR10

(Network Scanner Module for Document  
Distribution System is required)

**Network Scanner Module for  
Document Distribution System**  
DA-NS601

## Paper Feed Options

### Other Options

**Key Counter Cable Kit**  
DA-KH200

**Data Security Kit**  
DA-SC03

(Hard Disk Drive Unit and Image Memory are required)




## Full-Height Configurations

## For Wheelchair Configurations

### 2-Paper Tray Configuration

### 3-Paper Tray Configuration

### 4-Paper Tray Configuration



### 1- 3rd Paper Tray

DA-DS305

### 2- 4th Paper Tray

DA-DS306

### 3- Deluxe Stand (High)

DA1D310


### 4- Deluxe Stand (Low)

DA1D320

### 5- Base Plate with Casters

DA1D230

### 2-Paper Tray Configuration



### 3-Paper Tray Configuration



## DP-3030 Specifications

General	
Type	Desktop
Copy / Print Process	Laser Indirect Electrostatic
Developing Process	Dry Dual Component
Inverting Automatic Document Feeder	50 sheets (Letter, 20 lb, 75 g/m <sup>2</sup> )
Paper Feed	Std. 550-sheet paper tray unit: x 2 + 50-sheet bypass Max. 2,250 sheets with option
Paper Weight	Paper Tray: 16 to 24 lb (60 to 90 g/m <sup>2</sup> ) Bypass: 15 to 34 lb (55 to 133 g/m <sup>2</sup> )
Power Requirements	AC 120, 60 Hz, 12A
Power Consumption	Max.: Less than 1.5 kW Power saver mode: Approx. 28 W Sleep mode: Approx. 18 W
Warm-up Time (68°F/20°C)	Approx. 35 sec. (Main power switch ON) Approx. 30 sec. (Power saver mode)
Dimensions (W x D x H) <sup>1</sup> (Excluding optional equipment)	23.6" x 27.9" x 33.9" (597 x 707 x 860 mm) (Including Automatic Document Feeder and ADF mounting bracket)
Weight <sup>1</sup> (Excluding optional equipment)	Approx. 181 lb (82 kg)
Digital Copier	
First Copy Time	Approx. 4.5 sec. (Letter)
Resolution	600 dpi
Gray Scale	256 steps
Multi Copy Speed <sup>12</sup>	up to 30 cpm
Maximum Original Size	Ledger
Copy Size	Ledger-Invoice (fixed)
Copy Ratio	Enlargement (fixed) 200%, 155%, 129%, 121% Reduction (fixed) 79%, 77%, 65%, 61%, 50%
Zoom (variable)	25-400% (in 1% increments)
Multiple Copy	1 to 999, Automatic reset to 1
Exposure Control	Text, Text/Photo, Photo
Sort Memory (Standard)	16 MB
(Option)	Base Memory (16 MB) plus 64 MB / 128 MB (max. 144 MB) 12 GB (with optional HDD)

Printer	
Network Printer Interface	Ethernet 10Base-T/100Base-TX
Communication Protocol	TCP/IP (LPR, RAW, Port9100), SNMP, DHCP) IPX/SPX <sup>13, 14</sup> , (NDS, Bindery, NDPS), AppleTalk (PS), IPP (PCL, PS)
Local Printer Interface	USB
Printer Language (Standard)	Panasonic Printing System for Windows <sup>15, 16</sup> (Option) PCL 5e Emulation <sup>17, 18</sup> , PCL 6 Emulation <sup>14, 15</sup> Adobe <sup>®</sup> PostScript <sup>®3</sup> ™ <sup>16</sup>
Printing Speed <sup>12</sup>	up to 30 ppm
Paper Size	Paper Tray: Ledger-Invoice Bypass: Ledger-Invoice
Printing Resolution	1,200 dpi equivalent x 600 dpi (PCL, PS), 600 dpi x 600 dpi, 300 dpi x 300 dpi (PCL, PS, GDI)
Printer Memory	50 MB
PCL/PS Spool Memory	6 GB with optional HDD
Compatible Client Operating Systems	Windows Vista <sup>19</sup> /XP/2000/98/Me, Windows NT 4.0 Mac <sup>®</sup> OS 8.6-10.4 (PS Only) <sup>18</sup>
Compatible Network Operating Systems	Windows <sup>®</sup> 2000/Server 2003, NT 4.0, Novell 3.x/4.x/5.x/Unix (LPR/LPR), Linux (LPR/LPR), AS/400 (PCL, PS)
Network Scanner	
Network Scanner Interface	Ethernet 10Base-T/100Base-TX
Communication Protocol	TCP/IP (LPR, FTP)
Maximum Scanning Size	Ledger
Scanning Speed <sup>17</sup>	Approx. 30 ppm (Originals per minute - Letter portrait with ADF)
Scanning Resolution	150 dpi x 150 dpi, 300 dpi x 300 dpi, 600 dpi x 600 dpi
Compatible Operating Systems	Windows <sup>®</sup> Vista/XP/2000/98/Me, Windows <sup>®</sup> 2003, Windows NT <sup>®</sup> 4.0
Data Format	TIFF, PDF
G3 Fax (Option)	
Compatibility	ITU-T Group 3, ECM
Modem Speed	33.6-2.4 kbps with automatic fallback
Coding Scheme <sup>17</sup>	JBIG / MMR / MR / MH
Scanning Speed <sup>17</sup>	Approx. 0.7 sec. (Letter portrait in Standard or Fine mode with ADF)
Transmission Speed <sup>18</sup>	Approx. 2.7 sec.
Scanning Resolution	Standard: 203 dpi x 98 lpi (8 dots/mm x 3.85 lines/mm) Fine: 203 dpi x 196 lpi (8 dots/mm x 7.7 lines/mm) Super Fine: 406 dpi x 391 lpi (16 dots/mm x 15.4 lines/mm) 600 dpi 600 dpi x 600 dpi
Maximum Original Size	Ledger
Effective Scanning Width	10.7" (274 mm)
Recording Resolution	600 x 600 dpi
Standard Memory <sup>19</sup>	3 MB (approx. 180 pages)
Optional Memory <sup>19</sup>	Base memory plus 4 MB (320 page-s)/8 MB (640 pages) 200 (Max. 1,000 with optional HDD)
Speed Dials	
Internet Fax/Scan-to-Email <sup>10</sup>	
Compatibility	IEF RFC 3965, IITU-T I37 <sup>11</sup>
Communication Protocol	TCP/IP (SMTP, POP3, LDAP)
Network Connectivity	10Base-T/100Base-TX Ethernet
Data Format	TIFF (Profile S/P/J), PDF <sup>11</sup>

## Dimensions



## Notes

- Dimensions and weights are approximate.
- Speeds are contingent upon applications, machine configuration, and status. Individual speeds may vary.
- Compatible with Novell Netware<sup>®</sup> 3.4/5/6 and Novell Directory Services<sup>®</sup>.
- Printer Controller Module or Multi-Page Description Language Controller Module option required.
- Panasonic Printing System for Windows will be available in March 2007.
- PCL 5e Emulation and PCL 6 Emulation will be available in May 2007.
- Multi-Page Description Language Controller Module option required.
- Scanning speed applies to the feeding process from the top to the end of a single page text chart. The time for the feeding process does not include the time that it takes for the top edge of the page to reach the scanning point and page ejector. Time for entire scanning process is not applied.
- Transmission time applies to temporary transmission of text data using only ITU-T Image No. 1 between the same models at maximum modem speed. Transmission time may vary in actual usage. Usually public telephone lines can only support communication speeds of 28.8 kbps or lower.
- Via FAX, transmission speed may fall back to a slower speed.
- Based on ITU-T Image No. 1 scanned in Standard mode.
- Depending on the receiving machines capability, the document may not be correctly printed depending on the chosen resolution and document size.
- 11.37 Internet Fax only supports TIFF format.

Design and specifications are subject to change without notice.

Microsoft, Windows and Windows Vista are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.  
Adobe, PostScript and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries.  
Novell Netware<sup>®</sup> and Novell Directory Services<sup>®</sup> are registered trademarks of Novell Inc. in the United States and other countries.  
PCL is a registered trademark of Hewlett-Packard.  
All other brand or product names are the property of their respective holders.



**Common Criteria Validated EAL2  
Data Security Kit DA-SC03 V.1.01**  
The certification obtained for this product regarding information security indicates that, as a result of evaluation based on given evaluation criteria and evaluation method, the target of evaluation used for such evaluation has been determined to conform to the security assurance requirements.



Panasonic Communications Company of North America  
Unit of Panasonic Corporation of North America  
One Panasonic Way, Secaucus, NJ 07094  
For a local dealer, please call 1-800-742-8086  
panasonic.com/office



As an Energy Star<sup>®</sup> Partner, Panasonic has determined that this product meets the Energy Star<sup>®</sup> Guidelines for energy efficiency.

## ISO 9001 Quality Management System

Our business processes which produce document, information and network products, from manufacturing to marketing, conform to ISO9001 Quality Management Systems standard. Design, development, manufacture, installation, repair and maintenance of document, information and network products, their associated devices and consumables.

